USB AUDIO LOGGER

Record up to 16 Lines on any Windows Server



Installation is a snap:

- 1. Attach the logger to any analog audio source.
- 2. Attach a USB cable to a PC or Server.
- 3. Load the CD, adjust levels, and you're recording!

You'll have complete recordings of every call on up to 16 lines. Sort, access, email, and retrieve recordings from any PC on the network. Monitor live calls in real-time. Locate recordings instantly using Caller-ID, numbers dialed, DID extension, or DTMF signaling.

Everything you need to record is included, even the USB cable. Just add a Windows PC, and you're up and running! Call today and try your logger risk-free.

Tech Specs:

•	40dBm to +10dBm peak level
	Amphenol 50-pin, 25 pair.
Power	.90-130V 5.1W Standard stock
	220V - Specify when ordering.
Triggers	.Hook Voltage, VOX, Complex,
	Continuous, Timed, Sampled
CODECs	True telecom G.711 with brick.
	wall switched capacitor filter
Impedance	.>10K DC Blocked Input
Clock Accuracy	.+/- 20PPM
Dimensions	.5x1.75x19 "1-U" RETMA Rack
Shipping Weight	.10.1lbs
Warranty	.1 year standard
	6 year Optional
Part No	.F16

- · Records from outside phone lines, analog extensions, microphones or radios in perfect digital guality.
- Installs with a quick, simple connection between the phones and your server. Existing equipment is unaffected. No PBX programming or alteration is required.
- Calls may be securely accessed worldwide via your existing LAN.
- All recordings are individually time and date stamped for easy recall.
- Caller ID and touch tones are decoded for easy search and recall.
- Individually adjustable level controls give you crystal clear recording from a variety of signal sources.
- Calls from each line and day are organized in separate directories for quick access. Every recording includes a digital signature with time and date stamps for traceability.
- Automatic disk space management saves room for your most important calls. Old calls can be backed-up or optionally deleted to conserve disk space.
- On-screen level meters show activity on all channels.
- Call Analysis Software sorts recordings using DTMF signaling. Calls can be easily located using DID trunk numbers, Caller ID, or outbound number dialed.
- Calls are recorded in standard .wav (u-law G.711) format for playback on any PC or Mac using Media Player. No proprietary playback software is required.
- Real Time Player software provides instant recall and live monitoring of any channel from remote network workstations.
- Also available in a cost-effective 8-channel version.
- USB plug-and-play with Windows 7, XP, Vista, Server 2003, or 2008.



2695 Walsh Avenue, Santa Clara, CA 95051 Tel: (408) 330-5599, Fax: (408) 541-8459 www.digital-loggers.com

Applicable laws must be observed when recording. © 2004-2009 DLI. US patent 6,122,239, additional pending.

INCLUDED SOFTWARE

Set up and Configuration Wizard

An easy-to-use windows setup utility makes configuration a breeze.

Get it right the first time, even with little or no telecom experience.

			E	OLI MIL-T1 USB to T1 Audio L	ogger	
Line Summary / Selector				Line Settings	<- Arrows to change lines->	
Line Name	Mode I	MB/Day	Max GB	Days Usage	Line	Line09
PD Radio 1	VOX	48	5.0	104 48 MB / Day (104 days)	Line Name :	T-DS11
PD Radio 2	VOX	4	1.8	437 4 MB / Day (437 days)	Line Allocation (GB)	2.7
PD Radio 3	VOX	2	2.7	1345 2 MB / Day (1345 days)	Allocated Days	0
T-DP21	VOX	16	1.4	89 16 M8 / Day (89 days)	Mode	Vox
Fire 1	VOX	18	2,6	142 18 MB / Day (142 days)	Sign Pattern	11xx
Fire 2	VOX	6	0.8	130 6 MB / Day (130 days)	Trim Silence (disabled)	0
Fire 3	VOX	11	1.5	135 11 MB / Day (135 days)	12000000000000000000000000000000000000	-40
T-D531	VOX	1	2.1	2090 1 MB / Day (2090 days)	Enable Call Analysis	Yes
T-DS11	VOX	0	2.7	0	Usage	
Dispatch 1	VOX	5	8.0	1593 5 MB / Day (1593 days)	MB Per Day	0
Dispatch 2	VOX	0	6.7	0		
T-Outside 1	VOX	18	0.0	0 18 MB / Day (0 days)		
T-Outside 2	VOX	0	0.1	0		
Dispatch 3	VOX	.0	1.1	0		
R-SVC1	VOX	1		2299 1 MB / Day (2299 days)	4	1
R-SVC2	VOX	0	1.7	0	CilLogger Audio 238.5 G	10
R-SVC3	VOX	1	1.0	1019 1 MB / Day (1019 days)	Critcogger Audio 20015 G	Mile
R-TAC7	VOX	.0	2.5	0	21%	
R-TAC8	VOX	0	1.0	0		20%
<				>		

Recording Manager

The main logging application gives you a real-time display of incoming recordings.

Calls are neatly organized in daily directories. Disk space is automatically managed. One click leads you directly to the recordings for that line.

Drive L:\: 17.3% Used		
Ch Mode Name	dBm	
11 VOX 911 Dispatch	+01.5	
12 CNT Emergency Servi	+01.5	
13 VOX Fire Dispatch	+01.5	
14 VOX Jail Pay Phone	+01.5	
15 VOX 911Dispatch1	+01.5	
06 VOX 911	+01.5	
17 VOX SecondLine	+01.5	
18 VOX Line08	+01.5	
9 VOX Line09	+01.5	
0 VOX Line10	+01.5	
1 VOX Line11	+01.5	
2 VOX Line12	+01.5	
3 VOX Line13	+01.5	
4 VOX Line14	+01.5	
15 VOX Line15	+01.5	
6 VOX Line16	+01.5	
17 VOX Line17	+01.5	
8 VOX Line18	+01.5	
9 VOX Line19	+01.5	
20 VOX Line20	+01.5	
21 VOX Line21	+01.5	
22 VOX Line2	+01.5	
23 VOX Line23	+01.5	
24 VOX Line24	+01.5	

Evidence Builder Call Analyzer

Evidence Builder Software is a powerful program used to locate and analyze recordings in a spreadsheet format.

Use it to analyze incoming calls, create lists, sort calls, and search by time, date, line, DTMF, DID, nummber dialed, etc.

Quickly locate recordings on a local workstation or server. Copy, email, or transfer calls to an audio editor.

i.	No recording s						1
Date/Tin		Line		Number 🥥	Contraction Contraction Contraction	Incoming Caller ID -	^
2000 C	7 12:42:52	Line03	00:01:57		425-555-6100		-
23.50	and a second	Line02	00:03:00	1652			
5.0.000	3 12:42:27		00:00:14		1-515-555-4200		
1.	2 12:42:10		00:01:41	10000	1-920-555-7120		
8700 C		Line01	00:02:23	3283		662·555-7035	
10.00	2 12:38:09	Line06	00:03:05		1-631-555-1640		
	2 12:38:09	Line02	00:03:05	1640		631-555-1640	
1.000	2 12:37:59	Line08	00:02:24		1-888-555-0099		
	2 12:37:58	Line01	00:02:27	1640		631-555-1640	
10.000		Line09	00:01:11		775-555-7215		
		Line11	00:01:44		775-555-7215		
10000		Line12	00:02:53		1-918-555-0001		
	12:34:18	Line13	00:01:46		1-213-555-7111		×
Num Rei	ordings: 301		First: 10:00:24, 02	/11/2008	Last: 12:58:20,	02/11/2008	
Notes							

Live Remote Monitoring

Dispatch 1			~	
Date	Start time	End time	Length	TIC
10/30/2006	11:37:32 PM	11:38:23 PM	00:00:51	
0/30/2006	5:00:11 PM	5:02:06 PM	00:01:55	
0/30/2006	4:45:15 PM	4:46:09 PM	00:00:54	
0/30/2006	3:56:47 PM	3:57:12 PM	00:00:25	
0/30/2006	12:30:21 PM	12:31:29 PM	00:01:08	
				24
 - 18.0 -18.0	-14.0 -1	11.0]- 7.0 -8.9	-4.0 -4.2 -4.2] 0.0

Local or remote users can be assigned access priviledges to allow remote interception and live monitoring of calls.

Monitor locally via LAN or world-wide via WAN.

PBX Call Detail Recorder

Get detailed reports on every call, even internal calls from one PBX extension to another. Capture all the call detail information provided from your PBX serial port. Document calls between extensions.

ANI, ALI, or SMDR data streams are logged using our call detail recording utility. This program logs all serial data from up to 8 PBX or modem ports simultaneously.

폴 Digital	Loggers Inc	c. Call Detail I	Recorder					
<u>Eile E</u> dit <u>S</u> ervice <u>H</u> elp								
Instance	Port	Status	Auto Start	Log File				
1	COM1	Running	No	c:\E-911 ALI Log				
2	COM2	Stopped	No	c:\PBX SMDR Reports				
•				►.				
Ready				//				